



AHD-IP-960H HYBRID DVR

- Megapixel video signal over existing coaxial cable
- AHD(1080P/720P)&Analog 960H/760H Hybrid
- Free CMS integration with AHD/SDI/960H/IP...
- IOS/Android App for remote security



Model	DI-1624 4CH
Live Display	Realtime live display for 30/25fps each channel
Recording playback	IP cam : 1080P / 60fps ; 720P 120/100fps AHD : 1080P / 40fps ; 1080P-Lite / 720P 80fps 960H : 120 / 100fps
Split Screen	1/4 CH
Main monitor	HDMI, VGA , BNC x1
Call monitor	BNC x1
Audio input	1 RCA-jack connectors
Audio Output	1 RCA-jack connectors (up to 2 Vrms)
Freeze	Yes
Sequential switch	User adjustable
Live Digital Zoom	X2 X4
Watermark	Yes
Recording Mode	Manual/ Schedule / Motion / Alarm
Pre-record Mode	0-10 sec
Post-record time	0-60 minutes
Playback Search	Motion, Camera, Video Loss, Event, Date/Time, Smart search
Loss detection	Yes
Motion detection	Support configurable detection area & sensitivity
Buzzer	Yes
Alarm Input	2
Alarm Output	1 (NC or NO)
Alarm set/unset ; Panic	No
Push alarm notification	Yes, to mobile phones
I/R remote	Yes
RS-232	No
RS-485	2 PIN PTZ control
3G Dongle support	Yes
Storage HDD	1 x SATA HDDs (support 4TB/HDD)
Partitions	Configurable "Motion partition size" and "Auto-overwrite"
Backup	USB 2.0
Trigger	Video Loss, Motion, Alarm
Event log	Yes
Multi-Langage	Chinese/English/Japanese/French/Spanish / Polish/Russian Turkish/Greek/Portuguese/Korean/Italian/... ODM welcome
System recovery	Auto power on after power loss recovery
Watch Dog Timer	Yes
Network	RJ-45 10M/100M bps Ethernet connector
Web(GUI)	Remote setup, monitoring backup
	Remote software upgrade
	I.E software for Multiple DVRs (64ch Display on Screen)
	Configurable HTTP/Control/Data port
E-mail	Alarm notification to stationary or mobile devices
FTP	Alarm video/audio file storage
Video	1/ 4 split screen display & SEQ mode for I.E
	Electronics maps for CMS
Audio	Two directional
Protocol	TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP, TSP
Remote user	Up to login 8 User
Remote stations	PC base, smart phone, or PDA
Password Security	Multi-level password(4 levels, up to 18 accounts) protection
Dimension / Weight	195(W) x 220(D) x 45(H)mm / 2kgs
Power Consumption	+12VDC , 36W Max.
Temperature	0°C~ + 40°C



AHD-IP-960H Hybrid DVR



- Megapixel video signal over existing coaxial cable
- AHD(1080P/720P)&Analog 960H/760H Hybrid
- Free CMS integration with AHD/SDI/960H/IP...
- IOS/Android App for remote security



Model	DI-7928 8CH
Live Display	Realtime live display for 30/25fps each channel
Recording playback	IP cam : 1080P / 720P 120/100fps AHD : 1080P / 60fps ; 1080P-Lite / 720P 120fps 960H : 240 / 200fps
Split Screen	1/4/7/9 CH
Main monitor	HDMI, VGA , BNC x1
Call monitor	BNC x1
Audio input	4 RCA-jack connectors
Audio Output	1 RCA-jack connectors (up to 2 Vrms)
Freeze	Yes
Sequential switch	User adjustable
Live Digital Zoom	X2 X4
Watermark	Yes
Recording Mode	Manual/ Schedule / Motion / Alarm
Pre-record Mode	0-10 sec
Post-record time	0-60 minutes
Playback Search	Motion, Camera, Video Loss, Event, Date/Time, Smart search
Loss detection	Yes
Motion detection	Support configurable detection area & sensitivity
Buzzer	Yes
Alarm Input	8
Alarm Output	1 (NC or NO)
Alarm set/unset ; Panic	No
Push alarm notification	Yes, to mobile phones
I/R remote	Yes
RS-232	YES
RS-485	2 PIN PTZ control
3G Dongle support	Yes
Storage HDD	2 x SATA HDDs (support 4TB/HDD) HDD Extension for 1 eSATA connect
Partitions	Configurable "Motion partition size" and "Auto-overwrite"
Backup	USB 2.0
Trigger	Video Loss, Motion, Alarm
Event log	Yes
Multi-Language	Chinese/English/Japanese/French/Spanish Polish/Russian Turkish/Greek/Portuguese/Korean/Italian/...ODM welcome
System recovery	Auto power on after power loss recovery
Watch Dog Timer	Yes
Network	RJ-45 10/100 baseT Ethernet connector Remote setup, monitoring backup Remote software upgrade
Web(GUI)	I.E software for Multiple DVRs (64ch Display on Screen) Configurable HTTP/Control/Data port
E-mail	Alarm notification to stationary or mobile devices
FTP	Alarm video/audio file storage
Video	1/ 4/ 5/ 10 split screen display & SEQ mode for I.E Electronics maps for CMS
Audio	Two directional
Protocol	TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP, TSP
Remote user	Up to login 8 User
Remote stations	PC base, smart phone, or PDA
Password Security	Multi-level password(4 levels, up to 18 accounts) protection
Dimension / Weight	320(W) x 210(D) x 50(H)mm / 4 kgs
Power Consumption	+12VDC
Temperature	0°C~ + 40°C



AHD-IP-960H HYBRID DVR



- Megapixel video signal over existing coaxial cable
- AHD(1080P/720P)&Analog 960H/760H Hybrid
- Free CMS integration with AHD/SDI/960H/IP...
- IOS/Android App for remote security



Model	DI-7926 16CH
Live Display	Realtime live display for 30/25fps each channel
Recording playback	IP cam : 1080P / 180fps ; 720P 240/200fps AHD : 1080P / 120fps ; 1080P-Lite / 720P 240fps 960H : 480 / 400fps
Split Screen	1/ 4/7/9/10/13/16 CH
Main monitor	HDMI, VGA , BNC x1
Call monitor	BNC x1
Audio input	8 RCA-jack connectors
Audio Output	2 RCA-jack connectors (up to 2 Vrms)
Freeze	Yes
Sequential switch	User adjustable
Live Digital Zoom	X2 X4
Watermark	Yes
Recording Mode	Manual/ Schedule / Motion / Alarm
Pre-record Mode	0-10 sec
Post-record time	0-60 minutes
Playback Search	Motion, Camera, Video Loss, Event, Date/Time, Smart search
Loss detection	Yes
Motion detection	Support configurable detection area & sensitivity
Buzzer	Yes
Alarm Input	16
Alarm Output	4 (NC or NO)
Alarm set/unset ; Panic	Yes
Push alarm notification	Yes, to mobile phones
I/R remote	Yes
RS-232	Yes
RS-485	2 PIN PTZ control
3G Dongle support	Yes
Storage HDD	Basic 2 SATA HDD (support 4TB/HDD) 1 eSTAT HDD extension ; Two SATA HDD capacity optional
Partitions	Configurable "Motion partition size" and "Auto-overwrite"
Backup	USB 2.0
Trigger	Video Loss,Motion,Alarm
Event log	Yes
Multi-Langage	Chinese/English/Japanese/French/Spanish Polish/Russian Turkish/Greek/Portuguese/Korean/Italian/...ODM welcome
System recovery	Auto power on after power loss recovery
Watch Dog Timer	Yes
Network	RJ-45 10/100 baseT Ethernet connector Remote setup,monitoring backup Remote software upgrade
Web(GUI)	I.E software for Multiple DVRs (64ch Display on Screen) Configurable HTTP/Control/Data port
E-mail	Alarm notification to stationary or mobile devices
FTP	Alarm video/audio file storage
Video	1/ 4/ 5/ 10 split screen display & SEQ mode for I.E Electronics maps for CMS
Audio	Two directional
Protocol	TCP/IP,HTTP,PPPoE,DHCP,DDNS,FTP,TSP
Remote user	Up to login 8 User
Remote stations	PC base,smart phone,or PDA
Password Security	Multi-level password(4 levels,up to 18 accounts) protection
Dimension / Weight	350(W) x 345(D) x 60(H)mm / 4.5kgs
Power Consumption	+12VDC
Temperature	0°C~ + 40°C

SPECIFICATION ARE SUBJECT TO CHANGE WITHOUT NOTICE



AHD-IP-960H Hybrid DVR



- Megapixel video signal over existing coaxial cable
- AHD(1080P/720P)&Analog 960H/760H Hybrid
- Free CMS integration with AHD/SDI/960H/IP...
- IOS/Android App for remote security



Model	DI-7826 16CH
Live Display	Realtime live display for 30/25fps each channel
Recording playback	IP cam : 1080P / 180fps ; 720P 240/200fps AHD : 1080P / 120fps ; 1080P-Lite / 720P 240fps 960H : 480 / 400fps
Split Screen	1/ 4/7/9/10/13/16 CH
Main monitor	HDMI, VGA , BNC x1
Call monitor	BNC x1
Audio input	8 RCA-jack connectors
Audio Output	2 RCA-jack connectors (up to 2 Vrms)
Freeze	Yes
Sequential switch	User adjustable
Live Digital Zoom	X2 X4
Watermark	Yes
Recording Mode	Manual/ Schedule / Motion / Alarm
Pre-record Mode	0-10 sec
Post-record time	0-60 minutes
Playback Search	Motion, Camera, Video Loss, Event, Date/Time, Smart search
Loss detection	Yes
Motion detection	Support configurable detection area & sensitivity
Buzzer	Yes
Alarm Input	16
Alarm Output	4 (NC or NO)
Alarm set/unset ; Panic	Yes
Push alarm notification	Yes, to mobile phones
I/R remote	Yes
RS-232	Yes
RS-485	2 PIN PTZ control
3G Dongle support	Yes
Storage HDD	6 SATA HDD or 5 SATA HDD +1 e-SATA
Partitions	Configurable "Motion partition size" and "Auto-overwrite"
Backup	USB 2.0
Trigger	Video Loss,Motion,Alarm
Event log	Yes
Multi-Langage	Chinese/English/Japanese/French/Spanish Polish/Russian Turkish/Greek/Portuguese/Korean/Italian/...ODM welcome
System recovery	Auto power on after power loss recovery
Watch Dog Timer	Yes
Network	RJ-45 10/100 baseT Ethernet connector Remote setup,monitoring backup Remote software upgrade
Web(GUI)	I.E software for Multiple DVRs (64ch Display on Screen) Configurable HTTP/Control/Data port
E-mail	Alarm notification to stationary or mobile devices
FTP	Alarm video/audio file storage
Video	1/ 4/ 5/ 10 split screen display & SEQ mode for I.E Electronics maps for CMS
Audio	Two directional
Protocol	TCP/IP,HTTP,PPPoE,DHCP,DDNS,FTP,TSP
Remote user	Up to login 8 User
Remote stations	PC base,smart phone,or PDA
Password Security	Multi-level password(4 levels,up to 18 accounts) protection
Dimension / Weight	350(W) x 345(D) x 60(H)mm / 4.5kgs
Power Consumption	+12VDC
Temperature	0°C~ + 40°C

SPECIFICATION ARE SUBJECT TO CHANGE WITHOUT NOTICE