QIG: VMS – CarGisPlayer ver 5.3

Please prepare two PC with installed CarGisPlayer. One for Server.(Steps as server mode)

The other for Operation.(Steps as client mode)

*Download CarGisPlayer from CD or website.





Package protocol use often involves difficulties in the networks with firewalls and NAT. Before the VMS start work, please check the port was opened on the firewall as below:

PORT : 1200~1210, 2200~2210, 3300~3310

*Server mode setup

(1)Select "Settings" \rightarrow "Server/client".



(2)Select "Server Mode", then click "Login".

Server mode ○ C	lient
Server IP	
Password	Consul

(3)Select "settings" \rightarrow "User account" \rightarrow "Add GROUP", create new account.

Step1. Select " User Account "



Step2. Click " Add Group "

					×
USA	ABC	Group ID	Group Account	Group PassWord	
TW Tainei		0	ABC	12345678	
Australia					Add Group
Belize Chile					
France					Del Group
South Africa					
Thailand					

Step3. Create Account.

		×
Group ID: 10		
(Enter Capital lette	er only)	
Group Name	ASIA	
Group Account	TAIWAN	
Group PassWord	•••••	
ок	Ca	incel

Step4. Check settings.

USA	TAIWAN	Group ID	Group Account	Group PassWord
TW Australia		9	TAIWAN	12345678
Belize				
Chile France				
India				
South Africa Thailand				
ASIA				

Restart AP.





* Client mode setup

(1) Select "Settings" \rightarrow "Server/client".

Client			
File Win	ndows Contr	ol Sett	ings Help
🦰 🔍	😪 👝	6	Server/Client
			User Account
			Video-upload config
			Push Control
			Geofence editor
			Open/Close geofence
			Other

(2) Select "Client Mode" → input "Sever IP", "User ID" and "Password" then "Login" These information have to check above Server mode (3) Step 4

r mode	Oliei		
		π	
59 . 120	. 137	. 202	
TAIWAN			
•••••			
		Connect	
	59 . 120 TAIWAN	59 . 120 . 137 TAIWAN	59 . 120 . 137 . 202 TAIWAN

Example for Server mode (3) Step 4

USA	TAIWAN	Group ID	Group Account	Group PassWord	
TW Australia		9	TAIWAN	12345678	
Belize					 Add Group
-rance					Del Creur
ndia South Africa					Del Group
Thailand					
ASIA					
	1	I			

(3)Restart AP.



