

# KI-7638



## Specifications

<b>Image Sensor</b>	<b>Image Device</b>	1/2.9" SONY CMOS Sensor
	<b>Scan System</b>	Progressive Scan
	<b>Effective Pixel</b>	2592(H)x1944(V) 5M Pixels
<b>Lens</b>	<b>Mount</b>	Megapixel 6mm board lens(3.6mm option)
<b>Video Output</b>	<b>Output Resolution (AHD)</b>	2592X1944 @20 FPS
<b>OSD function</b>	<b>Min. Illumination</b>	0.1 Lux (@50IRE) / 0.01 Lux
	<b>Shutter Speed</b>	AUTO / 1/60(1/50) ~ 1/50,000sec
	<b>S/N Ration</b>	More than 50dB
	<b>AWB</b>	ATW / LOCK / MANUAL
	<b>WDR</b>	Off / D-WDR / BLC / HSBLIC
	<b>True Day &amp; Night</b>	Color / B&W / Auto / Extern
	<b>Camera Setting</b>	COM. / VIDEO OUTPUT MODE / LANGUAGE / FW VER.
	<b>Picture Adjustment</b>	SHARPNESS / COLOR GAIN / SHADING MIRROR / FLIP / DNR / DNR / MOTION
<b>Electricity</b>	<b>Power Consumption</b>	DC12V / <7W (without IR on)
<b>Mechanical</b>	<b>Dimension</b>	81(W) x80 (H) x 200 (D) mm
	<b>Weight</b>	310g
<b>Environment</b>	<b>Operation Temperature</b>	-10°C ~ +50°C
	<b>Humidity</b>	0%RH~80%RH